



DNAKE Intercom Product Comparison

DNAKE (Xiamen) Intelligent Technology Co., Ltd.

Easy and Smart Intercom



Contents

01

DNAKE VS Akuvox

02

DNAKE VS 2N

03

DNAKE VS Hikvision

04

DNAKE VS Dahua





PART 1

DNAKE VS Akuvox

CONFIDENTIAL




7" Screen Apartment Door Station

Items	DNAKE 905D-Y4 Pro	Akuvox R29S/R29C
Picture		
Front panel	Aluminum	Aluminum
Display	7" IPS capacitive touch screen	7 Inch capacitive touch screen
Camera	2 x 2MP HD Camera	3MP Main and 1MP Auxiliary Camera
IP rating	IP65	IP65
Wiegand/RS485	Yes	Yes
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
Installation	Semi-Flush mount	Flush mount & Surface mount
Dimension	227 x 122 x 20 mm	Flush mount: 324 x 130 x 60 mm Surface mount: 324 x 130 x 33 mm
Door open methods	Cards(100,000), passwords and faces(10,000), NFC	Cards, passwords and faces
Face recognition	Yes	Only available on R29C
Anti-spoofing	Yes	Yes
Operating System	Android	Android



4.3" Screen Apartment Door Station

Items	DNAKE S215	Akuvox R28A	Akuvox R27A
Picture			
Front panel	Aluminum	Aluminum	Aluminum
Display	4.3 Inch, color TFT LCD	4.3 Inch, color TFT LCD	Dot matrix LCD
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting	2M pixels, automatic lighting
Camera angle	110° (H)	116° (H)	116° (H)
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz & 125kHz	13.56MHz & 125kHz
IP/IK rating	IP65 / IK08	IP65 / Undisclosed	IP65 / Undisclosed
Wiegand/RS485	Yes	Yes	Yes
Induction loop	Yes	No	No
Relays out	3	3	3
Inputs	4 configurable	3	3
Vandal resistant	Yes	Yes	Yes
Installation	Flush mount & Surface mount	Flush mount & Surface mount	Flush mount & Surface mount
Dimension	Flush mount: 295 x 133 x 50.2 mm Surface mount: 295 x 133 x 42.7 mm	Flush mount: 280 x 130 x 68mm Surface mount: 280 x 130 x 38mm	Flush mount: 280 x 130 x 68mm Surface mount: 280 x 130 x 38mm



Villa(Second confirm) Door Station

Items	DNAKE 280SD-C12	Akuvox R20A	Akuvox R26C
Picture			
Front panel	Aluminum	Aluminum	Aluminum
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting	2M pixels, automatic lighting
IC card & NFC	Yes	Yes	Only IC card
IP/IK rating	IP65 / IK07	IP65 / Undisclosed	IP65 / Undisclosed
RS485	Yes	Yes	Yes
Relays out	Yes	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes	Yes
PoE	Yes	Yes	Yes
Installation	Flush mount & Surface mount	Flush mount & Surface mount	Flush mount & Surface mount
Dimension	Flush mount: 190 x 95 x 27 mm Surface mount: 170 x 84.5 x 31 mm	Flush mount: 189 x 120 x 56.5 mm Surface mount: 145 x 85 x 27.5 mm	Flush mount: 213 x 124 x 68 mm Surface mount: 190 x 110 x 40 mm



One-button Villa Door Station with keypad

Items	DNAKE S213K	Akuvox R20K
Picture		
Front panel	Aluminum	Aluminum
Dimension	Surface mount: 188 x 88 x 34 mm Flush mount: 230 x 120 x 48 mm	Surface mount: 185 x 85 x 29 mm Flush mount: 226 x 108 x 52 mm
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting
Camera angle	110° (H), 60° (V)	110° (H), 58° (V)
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz & 125kHz
Status Indicators	3	0
IP/IK rating	IP65 / IK08	IP65 / ✗
Tamper alarm	✓	✓
PoE	✓	✓
Ethernet port	RJ45, 10/100Mbps adaptive	RJ45, 10/100Mbps adaptive
Relays out	2	2
Inputs	2(Configurable)	2
Wiegand	✓	✓
RS485	✓	✓
Installation	Surface & Flush mount	Surface & Flush mount


Multi-button Villa Door Station

Items	DNAKE S213M	Akuvox R20B
Picture		
Front panel	Aluminum	Aluminum
Dimension	Surface mount: 188 x 88 x 34 mm Flush mount: 230 x 120 x 48 mm	Surface mount: 185 x 85 x 24 mm Flush mount: 226 x 108 x 52 mm
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting
Camera angle	110° (H), 60° (V)	110° (H), 58° (V)
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz & 125kHz
Buttons	5	5
Status Indicators	3	0
IP/IK rating	IP65 / IK08	IP65 / ✗
Tamper alarm	✓	✓
PoE	✓	✓
Ethernet port	RJ45, 10/100Mbps adaptive	RJ45, 10/100Mbps adaptive
Relays out	2	2
Inputs	2(Configurable)	2
Wiegand	✓	✓
RS485	✓	✓
Installation	Surface & Flush mount	Surface & Flush mount



Villa(Second confirm) Door Station

Items	DNAKE S212	Akuvox R20A
Picture		
Front panel	Aluminum	Aluminum
Dimension	Surface mount: 168 x 88 x 34 mm Flush mount: 210 x 120 x 48 mm	Surface mount: 145 x 85 x 27.5 mm Flush mount: 189 x 120 x 56.5 mm
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting
Camera angle	110°(H), 60°(V)	110°(H), 58°(V)
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz & 125kHz, NFC
Status Indicators	3	0
IP/IK rating	IP65 / IK08	IP65 / ✗
Tamper Alarm	✓	✓
PoE	✓	✓
Ethernet port	RJ45, 10/100Mbps adaptive	RJ45, 10/100Mbps adaptive
Relays out	2	2
Inputs	2(Configurable)	2
Wiegand	✓	✓
RS485	✓	✓
Installation	Surface & Flush mount	Surface & Flush mount



7" Screen Android Indoor Monitor

Items	DNAKE A416	Akuvox X933	IT82
Picture			
Display	7 Inch IPS LCD	7 Inch IPS LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1280 x 800	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic	Aluminum
RAM / ROM	1GB / 8GB	2GB / 8GB	2GB / 8GB
Operating system	Android 10	Android 9	Android 6
PoE	Yes	Yes	Yes
RS485	Yes	Yes	Yes
Relay out	1	2	1
Doorbell in	8(use any alarm input port)	1	0
I/O	8	8	8
WIFI	Optional	Optional	Optional
Camera	Optional 2MP camera	Optional 1MP camera	Optional 1MP camera
Mounting method	Surface & Desktop mount	Surface mount	Surface & Desktop mount
Dimension	189.5 x 132 x 26.4mm	205 x 148 x 27.5mm	232 x 160 x 27.8mm



7" Screen Android Indoor Monitor

Items	DNAKE E416	Akuvox C315
Picture		
Display	7 Inch TFT LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic
RAM / ROM	1GB / 8GB	1GB / 8GB
Operating system	Android 10	Android 6
PoE	Yes	Yes
RS485	Yes	Yes
Relay out	1	1
Doorbell in	8(use any alarm input port)	1
I/O	8	8
WIFI	Optional	Optional
Mounting method	Surface & Desktop mount	Surface & Desktop mount
Dimension	195 x 130 x 14.5mm	200.2 x 132.2 x 27.2mm

7" Screen Linux Indoor Monitor

Items	DNAKE E216	Akuvox C313
Picture		
Display	7 Inch TFT LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 800 x 480
Front panel	Plastic	Plastic
Operating system	Linux	Linux
PoE	Yes	Yes
RS485	Yes	Yes
Relay out	1	1
Doorbell in	8(use any alarm input port)	1
I/O	8	8
Mounting method	Surface & Desktop mount	Surface & Desktop mount
Dimension	195 x 130 x 14.5mm	200.2 x 132.2 x 27.2mm

7" Screen Linux Indoor Monitor

Items	DNAKE E217	Akuvox S562
Picture		
Front panel	Plastic	Plastic
Dimension	195 x 130 x 14.5mm	216.4 x 118.8 x 21.7mm
Screen display	7" TFT capacitive touch screen, 1024 x 600	7" TFT capacitive touch screen, 1024 x 600
RAM / ROM	128MB / 128MB	128MB / 128MB
Operating system	Linux	Linux
PoE	✓	✓
Dual Network Ports	Optional	✓
RS485	✓	✓
Relay out	1	1
Doorbell in	8(use any alarm input port)	1
I/O	8	8
WIFI	Optional	✗
Installation	Surface & Desktop mount	Surface & Desktop mount





PART 2



DNAKE VS 2N

CONFIDENTIAL



4.3" Screen Apartment Door Station

Items	DNAKE S215 / S415	2N IP Verso
Picture		
Front panel	Aluminum	Stainless steel
Display	4.3 Inch, color TFT LCD	4" touch LCD
Camera	2M pixels, automatic lighting	-
Camera angle	120° (H)	120° (H)
Face recognition	Yes	-
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz and 125kHz, NFC
IP/IK rating	IP65 / IK08	IP54 / IK08 (touchscreen IK7)
Wiegand/RS485	Yes	Yes
Induction loop	Yes(Integrated module)	Yes
Relays out	3	2
Inputs	4 configurable	2
Vandal resistant	Yes	Optional(need accessory)
Installation	Flush mount & Surface mount	Flush mount & Surface mount
Dimension	Flush mount: 295 x 133 x 50.2 mm Surface mount: 295 x 133 x 42.7 mm	Modular

7" Screen Android Indoor Monitor

Items	DNAKE A416	2N Indoor touch 2.0
Picture		
Display	7 Inch IPS LCD	7 Inch LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic
RAM / ROM	1GB / 8GB	-
Operating system	Android 10	Android 6
PoE	Yes	Yes
RS485	Yes	-
Relay out	1	2
Doorbell in	8(use any alarm input port)	2
I/O	8	-
WIFI	Optional	Optional
Camera	Optional 2MP camera	-
Mounting method	Surface & Desktop mount	Surface & Desktop mount
Dimension	189.5 x 132 x 26.4mm	205 x 148 x 27.5mm

7" Screen Linux Indoor Monitor

Items	DNAKE E216	2N Indoor View
Picture		
Display	7 Inch TFT LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic
Operating system	Linux	2N OS
PoE	Yes	Yes
RS485	Yes	-
Relay out	1	0
Doorbell in	8(use any alarm input port)	1
I/O	8	-
Mounting method	Surface & desktop mount	Flush, surface & desktop mount
Dimension	195 x 130 x 14.5mm	193 x 157 x 50 mm





PART 3




DNAKE VS Hikvision

CONFIDENTIAL



10.1" Screen Apartment Door Station

Items	DNAKE 902D-B6	Hikvision DS-KD9613-E6
Picture		
Display	10.1" capacitive touch screen	10" capacitive touch screen
Camera	2M pixels, automatic lighting	2 × 2 MP HD IR camera
IP rating	IP65	IP65
Wiegand/RS485	Yes	Only RS485
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
Installation	Flush mount	Flush mount
Dimension	400 x 180 x 45 mm	413 x 175.2 x 48.2 mm
Door open methods	Cards(100,000), passwords and faces(10,000), NFC	Cards(10,000), passwords and faces(5,000), NFC
Face recognition	Yes	Yes
Anti-spoofing	Yes	Yes
Operating System	Android	Linux



4.3" Screen face recognition Apartment Door Station

Items	DNAKE S415	Hikvision DS-KD9203-E6	Hikvision DS-KD9203-TE6
Picture			
Front panel	Aluminum	Plastic & glass	Plastic & glass
Display	4.3 Inch, color TFT LCD	4.3-inch colorful LCD	4.3-inch colorful LCD
Camera	2M pixels, automatic lighting	2 MP HD camera	2 MP HD camera
Camera angle	120° wide viewing angle	120° wide viewing angle	120° wide viewing angle
Face recognition	Yes(Max. 10000)	Yes(Max. 5000)	Yes(Max. 20000)
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz	13.56MHz
IP/IK rating	IP65 / IK08	IP65	IP65
Wiegand/RS485	Yes	Yes	Yes
Induction loop	Yes(Integrated module)	No	No
Relays out	3	1	2
Inputs	4 configurable	4	4
Vandal resistant	Yes	Yes	Yes
Installation	Flush mount & Surface mount	Flush mounting	Flush mounting
Dimension	Flush mount: 295 x 133 x 50.2 mm Surface mount: 295 x 133 x 42.7 mm	373 × 124 × 43.7 mm	373 × 124 × 43.7 mm



4.3" Screen Apartment Door Station

Items	DNAKE S215	Hikvision DS-KD8023-E6
Picture		
Front panel	Aluminum	Aluminum
Display	4.3 Inch, color TFT LCD	3.5-inch Colorful LCD
Camera	2M pixels, automatic lighting	2 MP HD camera
Camera angle	110° (H)	120°
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz
IP/IK rating	IP65 / IK08	IP65 / Undisclosed
Wiegand/RS485	Yes	Yes
Induction loop	Yes	No
Relays out	3	2
Inputs	4 configurable	4
Vandal resistant	Yes	Yes
Installation	Flush mount & Surface mount	Flush mount
Dimension	Flush mount: 295 x 133 x 50.2 mm Surface mount: 295 x 133 x 42.7 mm	418 × 145 × 59.7 mm




Villa(Second confirm) Door Station

Items	DNAKE 280SD-C12	DS-KV8113-WME1(B) / DS-KV8113-WME1(B)/Flush
Picture		
Front panel	Aluminum	Aluminum
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting
RF card reader	13.56MHz, NFC	13.56MHz
IP/IK rating	IP65 / IK07	IP65 / IK08
RS485	Yes	Yes
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
PoE	Yes	Yes
Installation	Flush mount & Surface mount	Flush mount & Surface mount
Dimension	Flush mount: 190 x 95 x 27 mm Surface mount: 170 x 84.5 x 31 mm	174 x 91 x 29 mm




Villa(Second confirm) Door Station

Items	DNAKE 280SD-R2	Hikvision DS-KV6113-PE1(B)
Picture		
Front panel	ABS	Plastic
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting
RF card reader	13.56MHz, NFC	13.56MHz
IP/IK rating	IP65	IP65
RS485	Yes	No
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
PoE	Yes	Yes
Installation	Surface mount	Surface mount
Dimension	170.5 x 111 x 38.6 mm	138 x 65 x 27 mm



7" Indoor Monitor

Items	DNAKE E416	DNAKE A416	DS-KH8350-TE1/WTE1
			
Display	7 Inch TFT LCD	7 Inch IPS LCD	7 Inch IPS LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic	Aluminum
RAM / ROM	1GB / 8GB	1GB / 8GB	128MB / 32MB
Operating system	Android 10	Android 10	Linux
PoE	Yes	Yes	Yes
RS485	Yes	Yes	Yes
Relay out	1	1	2
Doorbell in	8(use any alarm input port)	8(use any alarm input port)	-
I/O	8	8	8
WIFI	Optional	Optional	Optional
Camera	No	Optional 2MP camera	No
Mounting method	Surface & desktop mount	Surface & desktop mount	Surface mount
Dimension	195 x 130 x 14.5mm	189.5 x 132 x 26.4mm	180 x 140 x 22.4 mm

7" Android Indoor Monitor

Items	DNAKE E416W	DNAKE A416W	DS-KH9310-WTE1
Picture			
Display	7 Inch TFT LCD	7 Inch IPS LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic	Plastic
RAM / ROM	1GB / 8GB	1GB / 8GB	1GB / 4GB
Operating system	Android 10	Android 10	Android
PoE	Yes	Yes	Yes
RS485	Yes	Yes	Yes
Relay out	1	1	2
Doorbell in	8(use any alarm input port)	8(use any alarm input port)	-
I/O	8	8	8
WIFI	Optional	Optional	Yes
Camera	No	Optional 2MP camera	No
Mounting method	Surface & Desktop mount	Surface & Desktop mount	Surface mount
Dimension	195 x 130 x 14.5 mm	189.5 x 132 x 26.4mm	187 x 137 x 25.7 mm

7" Linux Indoor Monitor

Items	DNAKE E216	DS-KH6320-TE1/WTE1
Picture		
Display	7 Inch TFT LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	Plastic
Operating system	Linux	Linux
PoE	Yes	Yes
RS485	Yes	Yes
Relay out	1	2
Doorbell in	8(use any alarm input port)	-
I/O	8	8
Mounting method	Surface & Desktop mount	Surface mount
Dimension	195 x 130 x 14.5 mm	200 x 140 x 15.1 mm





PART 4



DNAKE VS Dahua

CONFIDENTIAL




10.1" Screen Apartment Door Station

Items	DNAKE 902D-B6	VTO9541D
Picture		
Display	10.1" capacitive touch screen	10" capacitive touch screen
Camera	2MP camera	2MP camera
IP rating	IP65	IP65
Wiegand/RS485	Yes	Yes
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
Installation	Flush mount	Flush mount
Dimension	400 x 180 x 45 mm	475.8 x 174.8 x 57.3 mm
Door open methods	Cards, passwords and faces, NFC	Cards, passwords and faces
Face recognition	Yes	Yes
Anti-spoofing	Yes	Yes
Operating System	Android	Linux



7" Screen Apartment Door Station

Items	DNAKE 905D-Y4 Pro	Dahua VTO7541G
Picture		
Front panel	Aluminum	Aluminum middle frame
Display	7" IPS capacitive touch screen	8" IPS capacitive touch screen
Camera	2 x 2MP HD Camera	2 x 2MP Camera
IP rating	IP65	IP66
Wiegand/RS485	Yes	Yes
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
Installation	Semi-Flush mount	Flush mount & Surface mount
Dimension	227 x 122 x 20 mm	389 x 145 x 43 mm
Door open methods	Cards(100,000), passwords and faces(10,000), NFC	Cards, passwords and faces, fingerprint
Face recognition	Yes	Yes
Anti-spoofing	Yes	Yes



4.3" Screen Door Station

Items	DNAKE S215	Dahua VTO6521F	DHI-VTO4202F-P-S2
Picture			
Front panel	Aluminum	Aluminum	Anodized aluminum front panel
Display	4.3" Screen Display	4.3" Screen Display	3.0" STN Display
Camera	2M pixels, automatic lighting	2M pixels, automatic lighting	2 MP HD camera
Camera angle	110° wide viewing angle	113.79° wide viewing angle	168.6° wide viewing angle
RF card reader	13.56MHz & 125kHz, NFC	13.56MHz	13.56MHz
IP/IK rating	IP65 / IK08	IP65 / IK07	IP65 / IK07
Wiegand/RS485	Yes	Yes	RS485
Induction loop	Yes	No	No
Relays out	3	1	1
Inputs	4 configurable	2	2
Vandal resistant	Yes	Yes	
Installation	Flush mount & Surface mount	Flush mount & Surface mount	Flush mount & Surface mount
Dimension	Flush mount: 295 x 133 x 50.2 mm Surface mount: 295 x 133 x 42.7 mm	389 ×145 ×41.9 mm	Modular




Villa(Second confirm) door station

Items	DNAKE 280SD-C12	VTO2201F-P
Picture		
Front panel	Aluminum	Aluminum
Camera	2MP HD Camera	2MP HD Camera
RF card reader	13.56MHz, NFC	13.56MHz
IP/IK rating	IP65 / IK07	IP65 / IK07
RS485	Yes	Yes
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
PoE	Yes	Yes
Installation	Flush mount & Surface mount	Flush mount & Surface mount
Dimension	Flush mount: 190 x 95 x 27 mm Surface mount: 170 x 84.5 x 31 mm	Product: 130 × 96 × 28.5 mm



Villa(Second confirm) door station

Items	DNAKE 280SD-R2	VTO2211G-P
Picture		
Front panel	ABS	PC+Acrylic
Camera	2MP HD Camera	2MP HD Camera
RF card reader	13.56MHz, NFC	13.56MHz
IP rating	IP65	IP65
RS485	Yes	Yes
Relays out	Yes	Yes
Exit Button/Door Magnetic	Yes	Yes
PoE	Yes	Yes
Installation	Surface mount	Surface mount
Dimension	170.5 x 111 x 38.6 mm	150 x 100 x 24.8 mm

7" indoor monitor

Items	DNAKE E416	VTH5321GB(W)-W	VTH8621KMS-WP
Picture			
Display	7 Inch TFT LCD	7 Inch TFT LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	PC+ABS	Metal
RAM / ROM	1GB / 8GB	-	-
Operating system	Android 10	Android 8.1	Linux
PoE	Yes	Yes	Yes
RS485	Yes	Yes	-
Relay out	1	0	0
Doorbell in	8(use any alarm input port)	8(use any alarm input port)	6(use any alarm input port)
I/O	8	8	6
WIFI	Optional	Yes	Yes
Camera	No	No	No
Mounting method	Surface & Desktop mount	Surface mount	Surface Mount
Dimension	195 x 130 x 14.5 mm	189.6 × 134.6 × 26 mm	185 × 147 × 23.5 mm

7" Linux indoor monitor

Items	DNAKE E216	VTH5421HB/VTH5421HW
Picture		
Display	7 Inch TFT LCD	7 Inch TFT LCD
Screen	7 Inch capacitive touch screen, 1024 x 600	7 Inch capacitive touch screen, 1024 x 600
Front panel	Plastic	PC+ABS
Operating system	Linux	Linux
PoE	Yes	Yes
RS485	Yes	Yes
Relay out	1	0
Doorbell in	8(use any alarm input port)	6(use any alarm input port)
I/O	8	6
Mounting method	Surface & Desktop mount	Surface mount
Dimension	195 x 130 x 14.5 mm	189.0 × 130.0 × 26.9 mm